

## Amendments of the Claims

The following listing of claims (if entered) will replace all prior versions, and listings, of claims in the above-identified patent application:

### Listing of Claims

1. (currently amended) A circuit that corrects errors in configuration data stored on a programmable logic device, the ~~programmable logic device~~ circuit comprising:  
a memory, incorporated in the programmable logic  
5 device, in which the configuration data and error check data associated with the configuration data ~~[[is]]~~ are stored; and  
error correction circuitry coupled to at least some of the memory to analyze the configuration data stored in the memory to determine if any values have changed after  
10 initial configuration of the memory and to correct any values that have changed; wherein:  
the configuration data are stored in an array including representative rows and representative columns of  
cells, each cell storing one bit of the configuration data; and  
15 the error check data are stored in a last additional representative column of cells and a last additional representative row of cells in the array, each cell storing one bit of the error check data.

2. (previously presented) The circuit of claim 1 wherein the error correction circuitry comprises at least one scrubbing circuit operative to:

- read from the memory a portion of the  
5 configuration data and an associated portion of the error check data; and  
apply an error correcting code on the portion of the configuration data and the associated portion of the error check data to determine whether at least one bit in the portion

10 of the configuration data has an error and to correct the at least one bit that has the error.

3. (original) The circuit of claim 2 wherein the scrubbing circuit is associated with a subset of the configuration data and an associated subset of the error check data.

4. (cancelled)

5. (currently amended) The circuit of claim [[4]] 1 wherein the error correction circuitry comprises:

first circuitry having an input operative to receive data from each cell in a representative row of the  
5 array and an output, the first circuitry generating a first parity for the data in the representative row at the output;  
second circuitry having an input operative to receive data from each cell in a representative column of the array and an output, the second circuitry generating a second  
10 parity for the data in the representative column at the output;  
third circuitry having a first input operative to receive the output of the first circuitry, having a second input operative to receive the output of the second circuitry, and an output, the third circuitry sending a signal at the  
15 output indicative of whether an error has occurred in a cell in the representative row and the representative column based on the first parity and the second parity; and  
fourth circuitry having a first input operative to receive the output of the third circuitry, a second input  
20 operative to receive data from the cell in the representative row and the representative column, and an output, the fourth circuitry sending a signal at the output having a correct value.

6. (original) The circuit of claim 5 wherein the correct value is:

the data from the cell when the output of the first logic gate indicates that no error has occurred; and  
5 the complement of the data from the cell when the output of the first logic gate indicates that the error has occurred.

7. (original) The circuit of claim 5 further comprising fifth circuitry operative to write the correct value into the cell.

8. (currently amended) The circuit of claim ~~[[4]]~~ 1 wherein the error correction circuitry comprises:

first circuitry having an input operative to receive data from all but one cell in a representative row of  
5 the array and an output, the first circuitry generating a first parity for the data from all but the one cell in the representative row at the output;

second circuitry having an input operative to receive data from all but the one cell in a representative  
10 column of the array and an output, the second circuitry generating a second parity for the data from all but the one cell in the representative column at the output; and

third circuitry having a first input operative to receive the output of the first circuitry, a second input  
15 operative to receive the output of the second circuitry, a third input operative to receive data from the one cell, and an output, the third circuitry generating a correct value at the output.

9. (original) The circuit of claim 8 further comprising fourth circuitry operative to write the correct value into the one cell.

10. (currently amended) ~~[[The]]~~ A circuit of claim 1 that corrects errors in configuration data stored on a programmable logic device, the circuit comprising:

5 a memory, incorporated in the programmable logic  
device, in which the configuration data and error check data  
associated with the configuration data are stored; and  
error correction circuitry coupled to at least  
some of the memory to analyze the configuration data stored in  
the memory to determine if any values have changed after  
10 initial configuration of the memory and to correct any values  
that have changed; wherein;

each bit of the configuration data is stored in  
a first cell, a second cell, and a third cell in the memory.

11. (original) The circuit of claim 10 wherein the  
error correction circuitry generates as output a same bit value  
that is stored in at least two of the first cell, the second  
cell, and the third cell.

12. (original) The circuit of claim 11 wherein the  
error correction circuitry comprises circuitry having a first  
input operative to receive a bit from the first cell, a second  
input operative to receive a bit from the second cell, a third  
5 input operative to receive a bit from the third cell, and an  
output, the circuitry generating a correct bit value at the  
output.

13. (original) The circuit of claim 12 further  
comprising second circuitry operative to write the correct bit  
value into at least one of the first cell, the second cell, and  
the third cell.

14. (currently amended) ~~[[The]]~~ A circuit of claim 1  
~~further~~ that corrects errors in configuration data stored on a  
programmable logic device, the circuit comprising:

a memory, incorporated in the programmable logic  
5 device, in which the configuration data and error check data  
associated with the configuration data are stored;

error correction circuitry coupled to at least  
some of the memory to analyze the configuration data stored in  
the memory to determine if any values have changed after  
10 initial configuration of the memory and to correct any values  
that have changed;

a resistive element coupled to an output of the  
error correction circuitry; and

a capacitive load coupled to the resistive  
15 element, wherein the resistive element and the capacitive load  
are operative to reduce static hazards associated with the  
error correction circuitry.

15. (original) The circuit of claim 14 wherein the  
resistive element is one of a polysilicon wire, a current  
starved pass gate, and a current starved inverter.

16. (original) A digital processing system  
comprising:

processing circuitry;

a memory coupled to the processing circuitry;

5 and

a programmable logic device as defined in  
claim 1 coupled to the processing circuitry and the memory.

17. (original) A printed circuit board on which is  
mounted a programmable logic device as defined in claim 16.

18. (original) The printed circuit board defined in  
claim 17 further comprising:

a memory mounted on the printed circuit board  
and coupled to the programmable logic device.

19. (original) The printed circuit board defined in  
claim 17 further comprising:

processing circuitry mounted on the printed  
circuit board and coupled to the programmable logic device.

20-23. (cancelled)

24. (original) A circuit that corrects errors in configuration data stored on a programmable logic device comprising:

a memory array of representative rows and  
5 representative columns of cells in which the configuration data and error check data associated with the configuration data are stored;

first circuitry having an input operative to receive data from each cell in a representative row of the  
10 array and an output, the first circuitry generating a first parity for the data in the representative row at the output;

second circuitry having an input operative to receive data from each cell in a representative column of the array and an output, the second circuitry generating a second  
15 parity for the data in the representative column at the output;

third circuitry having a first input operative to receive the output of the first circuitry, having a second input operative to receive the output of the second circuitry, and an output, the third circuitry sending a signal at the  
20 output indicative of whether an error has occurred in a cell in the representative row and the representative column based on the first parity and the second parity; and

fourth circuitry having a first input operative to receive the output of the third circuitry, a second input  
25 operative to receive data from the cell in the representative row and the representative column, and an output, the fourth circuitry sending a signal at the output having a correct value.

25. (original) The circuit of claim 24 wherein the correct value is:

the data from the cell when the output of the first logic gate indicates that no error has occurred; and

5                   the complement of the data from the cell when  
the output of the first logic gate indicates that an error has  
occurred.

26. (original) The circuit of claim 24 further  
comprising fifth circuitry operative to write the correct value  
into the cell.

27. (original) A circuit that corrects errors in  
configuration data stored on a programmable logic device  
comprising:

                  a memory array of representative rows and  
5 representative columns of cells in which the configuration data  
and error check data associated with the configuration data are  
stored;

                  first circuitry having an input operative to  
receive data from all but one cell in a representative row of  
10 the array and an output, the first circuitry generating a first  
parity for the data from all but the one cell in the  
representative row at the output;

                  second circuitry having an input operative to  
receive data from all but the one cell in a representative  
15 column of the array and an output, the second circuitry  
generating a second parity for the data from all but the one  
cell in the representative column at the output; and

                  third circuitry having a first input operative  
to receive the output of the first circuitry, a second input  
20 operative to receive the output of the second circuitry, a  
third input operative to receive data from the one cell, and an  
output, the third circuitry generating a correct value at the  
output.

28. (original) The circuit of claim 27 further  
comprising fourth circuitry operative to write the correct  
value into the one cell.

29-36. (cancelled)

37. (currently amended) A method for correcting errors in configuration data stored on a programmable logic device comprising:

- 5                   generating ~~and storing in a memory of the~~  
~~programmable logic device~~ error check data associated with the  
configuration data and storing the error check data in a  
memory, incorporated in the programmable logic device, in which  
the configuration data are stored;
- 10                   reading a portion of the configuration data and  
an associated portion of the error check data;  
                    determining if an error has occurred based on  
the portion of the configuration data and the associated  
portion of the error check data; and
- 15                   correcting the portion of the configuration data  
in response to the determining; wherein:  
                    the portion of the configuration data is at  
least two partial representative columns of cells in the memory  
that are physically non-contiguous.

38. (original) The method of claim 37 wherein the portion of the configuration data is at least one representative column of cells in the memory.

39. (original) The method of claim 37 wherein the portion of the configuration data is at least one partial representative column of cells in the memory.

40. (original) The method of claim 37 wherein the portion of the configuration data is at least two partial representative columns of cells in the memory that are physically contiguous.

41. (cancelled)



42. (original) The method of claim 37 wherein the determining comprises applying an error correcting code on the portion of the configuration data and the associated portion of the error check data.

43. (original) The method of claim 42 wherein the error correcting code is one of a Hamming Code, a Reed-Solomon Code, and a Product Code.

44. (original) The method of claim 37 wherein the correcting comprises writing the corrected portion of the configuration data into the memory.

45-53. (cancelled)

54-55. (not entered)